



CONOLIFT

#1 Quebec Drive, Seguin, ON P2A 0B2 Tel 888-480-3777 Fax 705-378-5068 Email sales@conolift.com

YH-30 MARINE HYDRAULIC HIGHWAY TRAILER

Effective Date:

02-Apr-18

Standard Capacities & Features

Capacity (size)..... Powerboats to 56' LOA
Capacity (weight)..... 60,000 lbs highway (maximum loaded speed rating of 50mph)
Heavy duty HSS steel tube frame
Hydraulic expanding width frame (expands from 55" - 101" inside)
Hydraulic HD double gooseneck (with 2" SAE pin)
Hydraulic lift - wheel and tongue lift with frame heights to 58"
Hydraulic Power: 11 HP Honda gasoline engine with electric start
Pilot operated safety lock-valves on all lift functions
Hydraulically operated keel support straps - one in forward frame, one at rear
12 adjustable powerboat pads
O-ring boss and JIC hydraulic fittings
Rear 4-pad equalizing rockers
Zinc coated steel hose ends and fittings
High strength hydraulic cylinder shafts
Stainless steel hardware (nuts/bolts/pins)
Nitrogen ride suspension system
MTO/DOT approved lighting package (includes center frame-mounted turn signals)
LED lights with marine grade wiring
Extendable rear tail-lights featuring built-in amber strobes
Power outlet at rear of trailer for additional marker/strobe lights
Air / hydraulic braking system with anti-lock (as required by MTO/DOT)
Tires: 245/70R17.5 radials - - 18 rims & tires total (including 2 spares)
Storage mount for spare tires
Flexible rubber fenders
Complete sandblast to white metal, **1 coat zinc primer, 1 coat epoxy high build primer**
Polyurethane paint - **2 coats of Conolift Red** PPG commercial performance paint
3 year warranty on frame, 2 years on hydraulic components with 90 days limited warranty on running gear

Optional Equipment

Custom PPG colour choice - 189 colors to choose from
Black or white decal (company name & telephone number) on both sides of unit
Air-ride suspension system
Aluminum rims
Stainless steel hose ends & fittings package includes stainless steel cyl. shafts
Wireless remote control 7 Functions
Hot dip galvanized frame and components (in lieu of standard painting process)

Prices are subject to change without notice. Conolift reserves the right to change specifications or substitute components as required in an effort to supply a better product in an ever changing marketplace.