



#1 Quebec Drive, Seguin, ON P2A 0B2 Tel 888-480-3777 Fax 705-378-5068 Email sales@conolift.com

YH-60 MARINE HYDRAULIC HIGHWAY TRAILER

Effective Date:
02-Apr-18

Standard Capacities & Features

- Capacity (size)..... Powerboats to 75' LOA
- Capacity (weight)..... 120,000 lbs highway (maximum loaded speed rating of 45mph)
- 16" x 16" x .500" HSS steel tube frame
- Hydraulic expanding width frame (expands from 63" - 110" clear inside width)
- Double hydraulic low-profile gooseneck
- Hydraulic lift - wheel and tongue lift with frame heights to approximately 60"
- Hydraulic Power: 20 HP Honda gasoline engine with electric start
- Pilot operated safety lock-valves on main frame lift
- Hydraulically operated fore and aft keel support straps
- Removable (hinged) forward frame expansion and alignment bar
- Forward frame features outside pockets for extra pad locations
- Rear 4-pad equalizing rockers
- Mid-frame hydraulically adjustable 4-pad equalizing rockers
- 16 adjustable powerboat pads
- O-ring boss and JIC hydraulic fittings
- Zinc coated steel hose ends and fittings
- High strength hydraulic cylinder shafts
- Stainless steel hardware (nuts/bolts/pins)
- Nitrogen ride suspension system
- MTO/DOT approved lighting package (includes built-in rear strobe lights)
- LED lights with marine grade wiring
- Extendable rear tail lights and mid-frame mounted turn signals
- Power outlet at rear of trailer for additional marker/strobe lights
- Air / hydraulic braking system with anti-lock (as required by MTO/DOT)
- Tires: 245/70R17.5 radials - - 28 rims & tires total (includes 4 spares)
- Rubber fenders
- Complete sandblast to white metal, **1 coat zinc primer, 1 coat epoxy high build primer**
- Polyurethane paint - **2 coats of Conolift Red** PPG commercial performance paint
- 3 year warranty on frame, 2 years on hydraulic components with 90 days limited warranty on running gear

Optional Equipment

- Custom PPG colour choice - 189 colors to choose from
- Black or white decal (company name & telephone number) on both sides of unit
- Wireless remote control 10 Functions
- Hot dip galvanized frame and components (in lieu of standard painting process)

Prices are subject to change without notice. Conolift reserves the right to change specifications or substitute components as required in an effort to supply a better product in an ever changing marketplace.