



CONOLIFT

#1 Quebec Drive, Seguin, ON P2A 0B2 Tel 888-480-3777 Fax 705-378-5068 Email sales@conolift.com

MML-80 MARINE MOBILE LIFT

Effective Date
1-Apr-15

Capacities & Features

Capacity (weight) -160,000 lbs. (72,700kgs)

Standard Dimensions: (can be adjusted to meet requirements)

Height Overall 26' 6"

Clear Height 24'

Width Overall 27' 6"

Clear Width (inside) 21'

Wheel Base 23' 6"

Cable Drop (into well) 12'

Frame: - Open end HSS frame, with forward mounted crossbeam & equalizing joint to relieve stress
- Large fuel and hydraulic tanks are integral in main frame construction

Power Unit: 100 HP CAT Diesel

Drive System: Full hydrostatic drive with dynamic braking (multi wet-disk parking brake)

Stainless steel hydraulic tubing

Travel Speed: Variable from 0 to 100' per minute

Grade Capability: Maximum 5% incline

Lift Speed: From 1' to 20' per minute (2 speed winches)

Steering: 90 degree steering capability

Pilot operated safety lock-valves on each winch

Operators Station: Gondola style with controls for all functions, including full engine instrumentation
Four point lift functions can be simultaneously or independently operated

Slings: 4 - 12" center-disconnect slings with hydraulic fore / aft adjustment

Tires: 54" x 16" 28 ply lug tread industrial tires

Forward and backwards motion alarm

Digital load gauges (lbs. or kgs.)

Complete sandblast to white metal, **1 coat zinc primer, 1 coat epoxy high build primer**

Polyurethane paint - **2 coats of Conolift Red** PPG commercial performance paint

2 year warranty on frame / 1 year on hydraulic components / or 2000 hrs. whichever comes first

Delivery, set-up and operator training

Custom colour choice - 189 colors to choose from

Optional Equipment

Radio remote control

Four wheel steering

Cold weather package - includes engine and hydraulic heaters

Delivery, set up, and operator training

Conolift reserves the right to change specifications or substitute components as required in an effort to supply a better product in an ever changing marketplace.