



#1 Quebec Drive, Seguin, ON P2A 0B2 Tel 888-480-3777 Fax 705-378-5068 Email sales@conolift.com

OTR-30 MARINE HYDRAULIC TRAILER

**Effective Date:
01-Nov-13**

Standard Capacities & Features

- Capacity (size).....Powerboats to 50' LOA
Sailboats to 52' LOA
- Capacity (weight)..... 60,000 lbs highway
70,000 lbs off-road only
- Trailer Dimensions..... Overall trailer length..... 53'
Usable bed length..... 42' 4"
Overall trailer width..... 8' 6" (custom width frames also available)
Clear width between frame rails..... 32"
Frame size..... 12" x 12" x .500" HSS steel tube
Keel ride height..... 16"

- HD fifth-wheel gooseneck with 2 lockable aluminum storage boxes
- Complete hot dip galvanized frame including hubs, brake drums, and rims
- Wireless remote control for all functions including main lift, hydraulic arms, and brakes
Manual back-up control panel on trailer for all functions (secured in lockable cabinet)
- Air powered frame lift (lift range is from 13" - 21" over crossbeams)
- Hydraulic-powered front landing wheels
- 6 - Hydraulic arms featuring manual telescopic extension / rear arms rotate fore and aft
- Pilot operated safety lock valves on hydraulic arms and front landing wheels
- 8 - 6" x 6" oak crossbeams
- 6 - Aluminum light weight drop beams
- Air braking system with ABS (12-1/2" x 7-1/4" brakes) with remote control operation
- 3 - 22,500 lb. Dexter axles with Firestone air-ride
- Pressure-fed oil-filled hubs
- Tires: 245/70R17.5 - 13 rims & tires total (including spare)
- Rubber fenders
- Fore and aft flag holders
- MTO/DOT approved lighting package - LED lights
- L.E.D. Rear amber strobes
- Stainless steel hardware package includes stainless steel pivot shafts and oilite bronze bushings
- Stainless steel hydraulic fittings including cylinder shafts
- 2 year warranty on frame & hyd. components with 90 days limited warranty on lights, brakes, & running gear

Optional Equipment

- Black or white decal (company name & telephone number) on both sides of unit
- Stainless steel hydraulic cylinder barrels (c/w brass cylinder heads)

Conolift reserves the right to change specifications or substitute components as required in an effort to supply a better product in an ever changing marketplace.