



#1 Quebec Drive, Seguin, ON P2A 0B2 Tel 888-480-3777 Fax 705-378-5068 Email sales@conolift.com

SP-100 MARINE HYDRAULIC SELF-PROPELLED TRAILER

Effective Date:
01-Nov-13

Standard Capacities & Features

- Capacity (size)..... Powerboats to 90' LOA
Sailboats to 92' LOA
- Capacity (weight)..... 200,000 lbs off-road only
- 16" x 16" x .500" HSS steel tube frame - bridged construction
- Integral hydraulic front-end power unit
- Power: 120 HP CAT Diesel
- 60 degree steering
- Full hydrostatic drive with dynamic braking (multi wet-disk parking brake)
- Variable speed to 5 MPH
- Single lever joy-stick control
- Full engine instrumentation
- Hydraulic expanding width frame (expands from 65" to 95" inside the inner wheels)
- Hydraulic lift - wheel and tongue lift with keel bar heights from 12 1/2" to 42"
- Pilot operated safety lock-valves on main frame, tongue, and hydraulic arms
- Telescopic hydraulically operated rear cross-bar
- Ten - 8" x 8" aluminum keel support bars
- Six - telescopic (extendable) hydraulic arms
 - Forward arms pivot inward to accommodate narrow beam boats
- O-ring boss and JIC hydraulic fittings
- Zinc coated steel hose ends and fittings
- High strength hydraulic cylinder shafts
- Stainless steel hardware (nuts/bolts/pins)
- Walking beam suspension
- Tires: Front - 4 - 315/80R 22.5 tires
 - Rear - 28" premium wide-trac solid Titan tires
- Complete sandblast to white metal, **1 coat zinc primer, 1 coat epoxy high build primer**
- Polyurethane paint - **2 coats of Conolift Red** PPG commercial performance paint
- 3 year warranty on frame, 2 years on hydraulic components with 90 days limited warranty on running gear

Optional Equipment

- Custom PPG colour choice - 189 colors to choose from
- Black or white decal (company name & telephone number) on both sides of unit
- Wireless remote control
- Stainless steel hose ends & fittings package
 - Base Trailer
 - With Rear Wheel Drive
- Hot dip galvanized frame and hubs
- Rear wheel drive assist

Conolift reserves the right to change specifications or substitute components as required in an effort to supply a better product in an ever changing marketplace.