



CONOLIFT
AQUACULTURE
MARINE

CONOLIFT

#1 Quebec Drive, Seguin, ON P2A 0B2 Tel 888-480-3777 Fax 705-378-5068 Email sales@conolift.com

SP-80 MARINE HYDRAULIC SELF-PROPELLED TRAILER

Effective Date:
01-Nov-13

Standard Capacities & Features

Capacity (size)..... Powerboats to 80' LOA
Sailboats to 82' LOA

Capacity (weight)..... 160,000 lbs off-road only

16" x 16" x .500" HSS steel tube frame - bridged construction

Integral hydraulic front-end power unit

Power: 120 HP CAT Diesel

60 degree steering

Full hydrostatic drive with dynamic braking (multi wet-disk parking brake)

Variable speed to 5 MPH

Single lever joy-stick control

Full engine instrumentation

Hydraulic expanding width frame (expands from 66 1/2" to 96 1/2" inside the inner wheels)

Hydraulic lift - wheel and tongue lift with keel bar heights from 12 1/2" to 47"

Pilot operated safety lock-valves on main frame, tongue, and hydraulic arms

Telescopic hydraulically operated rear cross-bar

Eight - 8" x 8" aluminum keel support bars

Six - telescopic (extendable) hydraulic arms

Forward arms pivot inward to accommodate narrow beam boats

O-ring boss and JIC hydraulic fittings

Zinc coated steel hose ends and fittings

High strength hydraulic cylinder shafts

Stainless steel hardware (nuts/bolts/pins)

Walking beam suspension

Tires: Front - 4 - 315/80R 22.5 tires

Rear - 28" premium wide-trac solid Titan tires

Complete sandblast to white metal, **1 coat zinc primer, 1 coat epoxy high build primer**

Polyurethane paint - **2 coats of Conolift Red** PPG commercial performance paint

3 year warranty on frame, 2 years on hydraulic components with 90 days limited warranty on running gear

Optional Equipment

Custom PPG colour choice - 189 colors to choose from

Black or white decal (company name & telephone number) on both sides of unit

Wireless remote control

Stainless steel hose ends & fittings package

Hot dip galvanized frame and hubs

Rear wheel drive assist

Base Trailer
With Rear Wheel Drive

Conolift reserves the right to change specifications or substitute components as required in an effort to supply a better product in an ever changing marketplace.