



# CONOLIFT

#1 Quebec Drive, Seguin, ON P2A 0B2 Tel 888-480-3777 Fax 705-378-5068 Email [sales@conolift.com](mailto:sales@conolift.com)

## **SL-20 MARINE HYDRAULIC SLING LIFT YARD TRAILER**

**Effective Date:  
01-Nov-13**

### Standard Capacities & Features

Capacity (size)..... Powerboats to 46' LOA  
Sailboats to 48' LOA and 6' 6" draft

Capacity (weight)..... 40,000 lbs off-road only

10" x 10" x .500" HSS steel tube frame

Hydraulic expanding width frame (expands from 10' to 14' 6" inside of slings)  
(expands from 89" to 143" inside of tires)

Hydraulic tongue with 5' extending(manual) pintle ring

Hydraulic lift - wheel and tongue lift with frame heights to 58"  
- Sling lift of an additional 36" of lift

Hydraulic Power 9 HP Honda with electric start and 2 stage pump  
10 gallon hydraulic reservoir

Wireless radio remote control

Pilot operated safety lock-valves on all lift functions

4 hydraulic sling posts with 36" of lift each  
Front sling has hydraulic adjustment fore and aft 10' to 16' on centers  
2 center-disconnect slings with hull protector pads

Tires: 28" premium solid wide-trac solid Titan tires (outside)  
22" premium solid wide-trac solid Titan tires (inside)

Complete sandblast to white metal, **1 coat zinc primer, 1 coat epoxy high build primer**

Polyurethane paint - **2 coats of Conolift Red** PPG commercial performance paint

2 year warranty on frame, 2 years on hydraulic components with 90 days limited warranty on running gear

### Optional Equipment

Custom PPG colour choice - 189 colors to choose from

Black or white decal (company name & telephone number) on both sides of unit

Hitch with 5' hydraulic extending pintle ring

Self-propelled power unit

Salt water package - consisting of :

- Hot-dipped galvanized frame and components
- Stainless steel hose ends and fittings, hydraulic cylinder shafts

Conolift reserves the right to change specifications or substitute components as required in an effort to supply a better product in an ever changing marketplace.