



CONOLIFT
AQUACULTURE
MARINE

CONOLIFT

#1 Quebec Drive, Seguin, ON P2A 0B2 Tel 888-480-3777 Fax 705-378-5068 Email sales@conolift.com

Y-15 MARINE HYDRAULIC YARD TRAILER

Effective Date:
02-Apr-18

Standard Capacities & Features

- Capacity (size)..... Powerboats to 42' LOA
Cradled sailboats to 44' LOA
- Capacity (weight)..... 30,000 lbs off-road only
- 10" x 10" x .375" HSS steel tube frame
- Hydraulic expanding width frame (expands from 68" to 98" inside)
- Hydraulic tongue with pintle ring
- Hydraulic lift - wheel and tongue lift with frame heights to 55"
- Hydraulic Power: 6.5 HP Honda gasoline engine
- Pilot operated safety lock-valves on main frame lift
- Hydraulically operated rear keel support strap
- 8 adjustable powerboat pads; 3 telescopic cradle bars with fixtures
- O-ring boss and JIC hydraulic fittings
- Zinc coated steel hose ends and fittings
- High strength hydraulic cylinder shafts
- Stainless steel hardware (nuts/bolts/pins)
- Walking beam suspension
- Tires: 28" premium wide-trac solid Titan tires
- Complete sandblast to white metal, **1 coat zinc primer, 1 coat epoxy high build primer**
- Polyurethane paint - **2 coats of Conolift Red** PPG commercial performance paint
- 3 year warranty on frame, 2 years on hydraulic components with 90 days limited warranty on running gear

Optional Equipment

- Custom PPG colour choice - 189 colors to choose from
- Black or white decal (company name & telephone number) on both sides of unit
- Front sliding bow pads
- "L" cradle arms for more efficient cradle moving Set of 8
- Stainless steel hose ends & fittings package (includes SS cylinder shafts) Base Trailer
With Sail Arms
- Wireless remote control 6 Functions Base Trailer
10 Functions With Sail Arms
- Electric brake package - Dexter 10K drum brakes
- Hot dip galvanized frame & components (in lieu of standard painting process) Base Trailer
With Sail Arms
- Hydraulic 4-arm package with rear arm swivel for handling non-cradled sail boats

Prices are subject to change without notice. Conolift reserves the right to change specifications or substitute components as required in an effort to supply a better product in an ever changing marketplace.