



CONOLIFT
AQUACULTURE
MARINE

CONOLIFT

#1 Quebec Drive, Seguin, ON P2A 0B2 Tel 888-480-3777 Fax 705-378-5068 Email sales@conolift.com

Y-60 MARINE HYDRAULIC YARD TRAILER

Effective Date:
02-Apr-18

Standard Capacities & Features

- Capacity (size)..... Powerboats to 70' LOA
- Capacity (weight)..... 120,000 lbs off-road only
- 14" x 14" x .500" HSS steel tube frame
- Hydraulic expanding width frame (expands from 96" to 126" inside) () tires
- Hydraulic tongue with pintle ring
- Hydraulic lift - wheel and tongue lift with frame heights to 66"
- Hydraulic Power: 11 HP Honda gasoline engine
- Pilot operated safety lock-valves on main frame lift and tongue
- Hydraulically operated fore and aft keel support straps
- Rear 4-pad equalizing rocker system
- 12 adjustable powerboat pads
- O-ring boss and JIC hydraulic fittings
- Zinc coated steel hose ends and fittings
- High strength hydraulic cylinder shafts
- Stainless steel hardware (nuts/bolts/pins)
- Walking beam suspension
- Tires: 28" premium wide-trac solid Titan tires
- Complete sandblast to white metal, **1 coat zinc primer, 1 coat epoxy high build primer**
- Polyurethane paint - **2 coats of Conolift Red** PPG commercial performance paint
- 3 year warranty on frame, 2 years on hydraulic components with 90 days limited warranty on running gear

Optional Equipment

- Custom PPG colour choice - 189 colors to choose from
- Black or white decal (company name & telephone number) on both sides of unit
- Electric start
- Stainless steel hose ends & fittings package (includes SS cylinder shafts)

	Base Trailer
	With 6 Sail Arms
- Wireless remote control

7 Functions	Base Trailer
13 Functions	With 6 Sail Arms
- Hydraulic fifth wheel gooseneck (2" SAE pin)
- Hot dip galvanized frame & components (in lieu of standard painting process)

	Base Trailer
	With 6 Sail Arms
- Hydraulic arm package with rear arm swivel for handling non-cradled sailboats

	6 Sail Arm Package
--	--------------------

Prices are subject to change without notice. Conolift reserves the right to change specifications or substitute components as required in an effort to supply a better product in an ever changing marketplace.