



by **Knapik**  
INDUSTRIAL INC

#1 Quebec Drive, RR#2 Parry Sound, ON P2A 2W8 Tel 888-480-3777 Fax 705-378-5068 Email [sales@con-o-lift.com](mailto:sales@con-o-lift.com)

## **OTR-30 MARINE HYDRAULIC TRAILER**

Capacity (size) - Powerboats to 50' LOA

- Sailboats to 52' LOA

Capacity (weight) - 60,000 lbs highway

- 70,000 lbs off-road

**Trailer Dimensions:**

Overall trailer length - 53'

Usable bed length - 42' 4"

Overall trailer width - 8' 6" (custom width frames also available)

Clear width between frame rails - 32"

Frame size - 12" x 12" x .500" HSS steel tube

Keel ride height - 16"

HD fifth-wheel gooseneck with lockable aluminum storage boxes

Complete hot dip galvanized frame including hubs, brake drums, and rims

Wireless remote control for all functions including main lift, hydraulic arms, and brakes

Manual back-up control panel on trailer for all functions (secured in lockable cabinet)

Air powered frame lift (lift range is from 13" - 21" over crossbeams)

Hydraulic-powered front landing wheels

Six hydraulic arms featuring manual telescopic extension / rear arms rotate fore and aft

Pilot operated safety lock valves on hydraulic arms

Seven 6" x 6" oak crossbeams

Air braking system with ABS (12-1/2" x 7-1/4" brakes) with remote control operation

Three 22,500 lb Dexter axles with Firestone air-ride

Pressure-fed oil-filled hubs

Tires: 235/75R17.5 radials - load range "J" - 13 rims & tires total (including spare)

Rubber fenders

MTO/DOT approved lighting package - LED lights

Stainless steel hardware package includes stainless steel pivot shafts and oilite bronze bushings

Stainless steel hydraulic fittings including cylinder shafts

Two year warranty on frame and hydraulic components with 90 days limited warranty on lights, brakes, and running gear

Con-o-lift reserves the right to change specifications or substitute components as required in an effort to supply a better product in an ever changing marketplace.