



by **Knapik**
INDUSTRIAL INC

#1 Quebec Drive, RR#2 Parry Sound, ON P2A 2W8 Tel 888-480-3777 Fax 705-378-5068 Email sales@con-o-lift.com

YH-60 MARINE HYDRAULIC HIGHWAY TRAILER

Standard Capacities & Features

Capacity (size) - Powerboats to 75' LOA
Capacity (weight) - 120,000 lbs highway (maximum loaded speed rating of 45 mph)
16" x 16" x .500" HSS steel tube frame
Hydraulic expanding width frame (expands from 63" - 110" clear inside width)
Double hydraulic low-profile gooseneck
Hydraulic lift - wheel and tongue lift with frame heights to approximately 60"
Hydraulic Power: 20 HP Honda gasoline engine with electric start
Pilot operated safety lock-valves on main frame lift
Hydraulically operated fore and aft keel support straps
Removable (hinged) forward frame expansion and alignment bar
Forward frame features outside pockets for extra pad locations
Rear 4-pad equalizing rockers
Mid-frame hydraulically adjustable 4-pad equalizing rockers
16 adjustable powerboat pads
Stainless steel hardware package
Nitrogen ride suspension system
MTO/DOT approved lighting package - LED lights (includes built-in rear strobe lights)
Extendable rear tail lights and mid-frame mounted turn signals
Power outlet at rear of trailer for additional marker/strobe lights
Air / hydraulic braking system with anti-lock (as required by MTO/DOT)
Tires: 235/75R17.5 radials - - 28 rims & tires total (includes 4 spares)
Rubber fenders
2 year warranty on frame and hydraulic components with 90 days limited warranty on running gear

Optional Equipment

Wireless remote control for all 10 hydraulic functions
Hot dip galvanized frame and hubs

Con-o-lift reserves the right to change specifications or substitute components as required in an effort to supply a better product in an ever changing marketplace.